


Quick-Ally System



Quick-Ally Aluminium Perimeter scaffold is 'Australian Made' and is a more cost effective solution that will suit most applications.

Quick-Ally scaffold is ideal for painting, remedial work, construction, or anywhere where working at heights access is required in hard to reach areas that need the scaffold to be erected and dismantled safely and efficiently.



BENEFITS

- 450kg S.W.L per working bay. (Medium Duty)
- Faster erection and dismantle times
- Light weight material, therefore reducing transport and labour costs
- Stair Access, Stretcher Access or Ladder Access, the choice is yours
- Walk through access unlike other Aluminium systems.



Contact

P (03) 9587 5609 F (03) 9587 5614 E alscaf@allsystems.com.au W allsystems.com.au

M 16 Capital Court, Braeside, VIC 3195

Our in-house design team use IScaf scaffolding software to provide a detailed drawing to suit your access requirements.







PRODUCT SPECIFICATIONS

- 450kg Medium Duty SWL
- 3.0mm wall thickness/extruded aluminium tube on all components
- Engineered & approved to AS/NZS 1576 /1995 0.7m or 1.2m wide walk through platforms Polypropylene decks enabling strength, durability & minimal maintenance
- Integrated aluminium toeboards
- Hop up brackets
- Bridging beams providing up to 7.2m opening stair or ladder access
- Faster erection & dismantle times
- Light weight, reducing transport costs

SPECIFICATIONS

- Standards 1.0m, 1.5m, 2.0m, 2.5m, 3.0m & 4.0m
- Ledgers 0.7m, 1.2m, 1.8m,
 2.4m & 3.0m
- Transoms 0.7m & 1.2m
- Transom Centres 500mm
- Hop up brackets 400mm wide

ALUMINIUM TUBE

- 50mm outside diameter
- 3mm wall thickness on all components
- 6005AT5 Structural Aluminium